

SAFETY DATA SHEET

Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols
Product number 2564

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricant.

1.3. Details of the supplier of the safety data sheet

Supplier Chemodex Limited
 Canal Road
 Worksop
 Nottinghamshire
 S80 2EH
 01909 473301

1.4. Emergency telephone number

Emergency telephone +44 (0) 1476 567615 (MON TO FRI 09:00 - 17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Aerosol 1 - H222, H229
Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336
Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) F+; R12. Xi; R38. R52/53, R67


Human health Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.

Environmental The product contains a substance which is harmful to aquatic organisms.

Physicochemical Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is extremely flammable. Vapours may form explosive mixtures with air.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.
 H229 Pressurised container: may burst if heated
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols

Precautionary statements	<p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P261 Avoid breathing vapour/spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 Call a POISON CENTER/doctor if you feel unwell.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p>
Contains	<p>HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE, HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE, NAPHTHA (PETROLEUM), HYDROTREATED LIGHT</p>
Supplementary precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P273 Avoid release to the environment.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with national regulations.</p>

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PETROLEUM GASES, LIQUEFIED	30-60%
CAS number: 68476-85-7	EC number: 270-704-2
Classification	
Flam. Gas 1 - H220	
Press. Gas, Compressed - H280	
MINERAL OIL	10-30%
CAS number: —	
Classification	
Not Classified	

Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE	10-30%
CAS number: 64742-49-0 EC number: 921-024-6 REACH registration number: 01-2119475514-35-XXXX	
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 STOT SE 3 - H336 Aquatic Chronic 2 - H411	
HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE	1-5%
CAS number: 64742-49-0 EC number: 931-254-9 REACH registration number: 01-2119484651-34-XXXX	
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	1-5%
CAS number: 64742-49-0 EC number: 265-151-9	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304	
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.	1-5%
CAS number: 64742-95-6 EC number: 265-199-0	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	

Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols

NAPHTHA (PETROLEUM), HYDRODESULFURISED HEAVY <1% CAS number: 64742-82-1 EC number: 265-185-4
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411
METHANOL <1% CAS number: 67-56-1 EC number: 200-659-6
Classification Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.
Ingestion	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

Advice on general occupational hygiene Wash promptly with soap and water if skin becomes contaminated.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

MINERAL OIL

Long-term exposure limit (8-hour TWA): 5mg/m³ mist

Short-term exposure limit (15-minute): 10mg/m³ mist

WEL = Workplace Exposure Limit

Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE (CAS: 64742-49-0)

DNEL	Consumer - Oral; Long term systemic effects: 699 mg/kg/day
	Workers - Oral; Long term systemic effects: 773 mg/kg/day
	Workers - Dermal; Long term systemic effects: 773 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 699 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 608 mg/m ³

HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE (CAS: 64742-49-0)

DNEL	Consumer - Oral; Long term systemic effects: 1301 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 1377 mg/kg/day
	Workers - Dermal; Long term systemic effects: 13964 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 1131 mg/m ³
	Workers - Inhalation; Long term systemic effects: 5306 mg/m ³

METHANOL (CAS: 67-56-1)

DNEL	Consumer - Oral; Short term systemic effects: 8 mg/kg/day
	Consumer - Oral; Long term systemic effects: 8 mg/kg/day
	Consumer - Dermal; Short term systemic effects: 8 mg/kg/day
	Workers - Dermal; Short term systemic effects: 40 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 8 mg/kg/day
	Workers - Dermal; Long term systemic effects: 40 mg/kg/day
	Consumer - Inhalation; Short term local effects: 50 mg/m ³
	Consumer - Inhalation; Short term systemic effects: 50 mg/m ³
	Workers - Inhalation; Short term systemic effects: 260 mg/m ³
	Workers - Inhalation; Short term local effects: 260 mg/m ³
	Consumer - Inhalation; Long term local effects: 50 mg/m ³
	Workers - Inhalation; Long term local effects: 260 mg/m ³
	Consumer - Inhalation; Long term systemic effects: 50 mg/m ³
Workers - Inhalation; Long term systemic effects: 260 mg/m ³	
PNEC	- Fresh water; 154 mg/l
	- Marine water; 15.4 mg/l
	- STP; 100 mg/l
	- Soil; 23.5 mg/kg

8.2. Exposure controls

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection	No specific hand protection recommended.
Other skin and body protection	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
Respiratory protection	No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Black.

Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols

Odour	Solvent.
Odour threshold	No information available.
pH	No information available.
Melting point	No information available.
Initial boiling point and range	-41 (-41 TO 300)°C @
Flash point	-40°C CC (Closed cup).
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.7 % Upper flammable/explosive limit: 44.0 %
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	0.73
Solubility(ies)	Insoluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	235°C
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Oxidising properties	No information available.
<u>9.2. Other information</u>	
Other information	None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability The product may not be stable under some conditions of storage or use.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid None known.

10.6. Hazardous decomposition products

Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols

Hazardous decomposition products None at ambient temperatures.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 35,714.28571429

Acute toxicity - dermal

ATE dermal (mg/kg) 107,142.85714286

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 1,071.42857143

Inhalation May cause drowsiness or dizziness. Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.

Skin contact Causes skin irritation.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health hazards No known chronic or acute health risks.

Route of entry Inhalation Skin and/or eye contact

Toxicological information on ingredients.

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,001.0

Species Rat

ATE oral (mg/kg) 5,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,001.0

Species Rabbit

ATE dermal (mg/kg) 2,001.0

HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,001.0

Species Rat

ATE oral (mg/kg) 5,001.0

Acute toxicity - dermal

Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols

Acute toxicity dermal (LD₅₀ 2,001.0 mg/kg)

Species Rabbit

ATE dermal (mg/kg) 2,001.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 21.0

Species Rat

ATE inhalation (vapours mg/l) 21.0

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 6,801.0 mg/kg)

Species Rat

ATE oral (mg/kg) 6,801.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 3,401.0 mg/kg)

Species Rat

ATE dermal (mg/kg) 3,401.0

METHANOL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 2,001.0 mg/kg)

Species Rat

ATE oral (mg/kg) 100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,001.0 mg/kg)

Species Rabbit

ATE dermal (mg/kg) 300.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 21.0

Species Rat

Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols

ATE inhalation (vapours 3.0
mg/l)

SECTION 12: Ecological Information

12.1. Toxicity

Ecological information on ingredients.

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

Acute toxicity - fish	LOEC, : 1-10 mg/l, Fish
Acute toxicity - aquatic plants	LOEC, : 10-100 mg/l, Algae
Acute toxicity - microorganisms	LOEC, : 1-10 mg/l, Activated sludge

HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE

Acute toxicity - fish	LOEC, : 10-100 mg/l, Fish
Acute toxicity - aquatic plants	LOEC, : 10-100 mg/l, Algae

METHANOL

Acute toxicity - fish	LC ₅₀ , 96 hours: >7900 mg/l, Fish
Acute toxicity - aquatic invertebrates	EC ₅₀ , 24 hours: 7600 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , : >500 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No data available

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols

Disposal methods Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Chemodex Limited - OGL Open Gear Lubricant 500ml Aerosols

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	12/08/2015
Revision	2
Supersedes date	19/05/2014
SDS number	4587
Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated H280 Contains gas under pressure; may explode if heated. H301 Toxic if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H315 Causes skin irritation. H331 Toxic if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H370 Causes damage to organs . H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.