

## SAFETY DATA SHEET

### Chemodex Limited - Chemcut Metal Working Compound 500ml Aerosols

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** Chemodex Limited - Chemcut Metal Working Compound 500ml Aerosols  
**Product number** 2594

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Lubricant.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Chemodex Limited  
 Canal Road  
 Worksop  
 Nottinghamshire  
 S80 2EH  
 01909 473301

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1909 473 301 (Hours 09:00 - 17:00 Mon to Fri)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** Not Classified  
**Environmental hazards** Aquatic Chronic 3 - H412

**Classification (67/548/EEC or 1999/45/EC)** F+; R12, R52/53

**Human health** Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.

**Environmental** The product contains a substance which is harmful to aquatic organisms.

**Physicochemical** Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is extremely flammable. Vapours may form explosive mixtures with air.

##### 2.2. Label elements

###### Pictogram



**Signal word** Danger

**Hazard statements** H222 Extremely flammable aerosol.  
 H229 Pressurised container: may burst if heated  
 H412 Harmful to aquatic life with long lasting effects.

## Chemodex Limited - Chemcut Metal Working Compound 500ml Aerosols

<b>Precautionary statements</b>	<p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P261 Avoid breathing vapour/spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p>
<b>Supplementary precautionary statements</b>	<p>P273 Avoid release to the environment.</p> <p>P501 Dispose of contents/container in accordance with national regulations.</p>

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>PETROLEUM GASES, LIQUEFIED</b>	<b>10-30%</b>
CAS number: 68476-85-7                      EC number: 270-704-2	
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas, Compressed - H280	
<b>MINERAL OIL</b>	<b>10-30%</b>
CAS number: —	
<b>Classification</b> Not Classified	
<b>NAPHTHA (PETROLEUM), HYDROTREATED LIGHT</b>	<b>1-5%</b>
CAS number: 64742-49-0                      EC number: 265-151-9	
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304	
<b>SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.</b>	<b>1-5%</b>
CAS number: 64742-95-6                      EC number: 265-199-0	
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	

## Chemodex Limited - Chemcut Metal Working Compound 500ml Aerosols

<b>NAPHTHA (PETROLEUM), HYDRODESULFURISED HEAVY</b> <span style="float: right;"><b>1-5%</b></span>
CAS number: 64742-82-1                      EC number: 265-185-4
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411
<b>METHANOL</b> <span style="float: right;"><b>&lt;1%</b></span>
CAS number: 67-56-1                      EC number: 200-659-6
<b>Classification</b> Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.
<b>Skin contact</b>	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

#### 4.2. Most important symptoms and effects, both acute and delayed

**General information**                      See Section 11 for additional information on health hazards.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor**                      Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media**      Foam, carbon dioxide or dry powder.

#### 5.2. Special hazards arising from the substance or mixture

## Chemodex Limited - Chemcut Metal Working Compound 500ml Aerosols

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

**Advice on general occupational hygiene** Wash promptly with soap and water if skin becomes contaminated.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### PETROLEUM GASES, LIQUEFIED

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

#### MINERAL OIL

Long-term exposure limit (8-hour TWA): 5mg/m<sup>3</sup> mist

Short-term exposure limit (15-minute): 10mg/m<sup>3</sup> mist

WEL = Workplace Exposure Limit

## Chemodex Limited - Chemcut Metal Working Compound 500ml Aerosols

### METHANOL (CAS: 67-56-1)

<b>DNEL</b>	Consumer - Oral; Short term systemic effects: 8 mg/kg/day
	Consumer - Oral; Long term systemic effects: 8 mg/kg/day
	Consumer - Dermal; Short term systemic effects: 8 mg/kg/day
	Workers - Dermal; Short term systemic effects: 40 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 8 mg/kg/day
	Workers - Dermal; Long term systemic effects: 40 mg/kg/day
	Consumer - Inhalation; Short term local effects: 50 mg/m <sup>3</sup>
	Consumer - Inhalation; Short term systemic effects: 50 mg/m <sup>3</sup>
	Workers - Inhalation; Short term systemic effects: 260 mg/m <sup>3</sup>
	Workers - Inhalation; Short term local effects: 260 mg/m <sup>3</sup>
	Consumer - Inhalation; Long term local effects: 50 mg/m <sup>3</sup>
	Workers - Inhalation; Long term local effects: 260 mg/m <sup>3</sup>
	Consumer - Inhalation; Long term systemic effects: 50 mg/m <sup>3</sup>
	Workers - Inhalation; Long term systemic effects: 260 mg/m <sup>3</sup>
<b>PNEC</b>	- Fresh water; 154 mg/l
	- Marine water; 15.4 mg/l
	- STP; 100 mg/l
	- Soil; 23.5 mg/kg

### 8.2. Exposure controls

<b>Eye/face protection</b>	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
<b>Hand protection</b>	No specific hand protection recommended.
<b>Other skin and body protection</b>	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
<b>Respiratory protection</b>	No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Black.
<b>Odour</b>	Solvent.
<b>Odour threshold</b>	No information available.
<b>pH</b>	No information available.
<b>Melting point</b>	No information available.
<b>Initial boiling point and range</b>	-41 (-41 TO 300)°C @
<b>Flash point</b>	-40°C CC (Closed cup).
<b>Evaporation rate</b>	No information available.
<b>Evaporation factor</b>	No information available.
<b>Flammability (solid, gas)</b>	No information available.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 0.7 % Upper flammable/explosive limit: 44.0 %

## Chemodex Limited - Chemcut Metal Working Compound 500ml Aerosols

Vapour pressure	No information available.
Vapour density	No information available.
Relative density	394
Solubility(ies)	Insoluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	235°C
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Oxidising properties	No information available.

### 9.2. Other information

Other information	None.
-------------------	-------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
------------	------------------------------------------------------------------------------------------------

### 10.2. Chemical stability

Stability	The product may not be stable under some conditions of storage or use.
-----------	------------------------------------------------------------------------

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None known.
------------------------------------	-------------

### 10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.
---------------------	------------------------------------------------------------------------------------------------------------------------------

### 10.5. Incompatible materials

Materials to avoid	None known.
--------------------	-------------

### 10.6. Hazardous decomposition products

Hazardous decomposition products	None at ambient temperatures.
----------------------------------	-------------------------------

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

ATE oral (mg/kg)	17,921.14695341
------------------	-----------------

#### Acute toxicity - dermal

ATE dermal (mg/kg)	53,763.44086022
--------------------	-----------------

#### Acute toxicity - inhalation

ATE inhalation (vapours mg/l)	537.6344086
-------------------------------	-------------

## Chemodex Limited - Chemcut Metal Working Compound 500ml Aerosols

<b>Inhalation</b>	Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.
<b>Skin contact</b>	No significant hazard at normal ambient temperatures.
<b>Eye contact</b>	Vapour or spray in the eyes may cause irritation and smarting.
<b>Acute and chronic health hazards</b>	No known chronic or acute health risks.
<b>Route of entry</b>	Inhalation Skin and/or eye contact

### Toxicological information on ingredients.

#### SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 6,801.0

Species Rat

ATE oral (mg/kg) 6,801.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 3,401.0

Species Rat

ATE dermal (mg/kg) 3,401.0

#### METHANOL

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 2,001.0

Species Rat

ATE oral (mg/kg) 100.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 2,001.0

Species Rabbit

ATE dermal (mg/kg) 300.0

##### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 21.0

Species Rat

ATE inhalation (vapours mg/l) 3.0

## Chemodex Limited - Chemcut Metal Working Compound 500ml Aerosols

### 12.1. Toxicity

#### Ecological information on ingredients.

#### METHANOL

<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 96 hours: >7900 mg/l, Fish
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 24 hours: 7600 mg/l, Daphnia magna
<b>Acute toxicity - aquatic plants</b>	EC <sub>50</sub> , : >500 mg/l, Algae

### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

### 12.3. Bioaccumulative potential

**Partition coefficient** No information available.

### 12.4. Mobility in soil

**Mobility** No data available

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Dispose of waste product or used containers in accordance with local regulations

**Disposal methods** Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.

## SECTION 14: Transport information

### 14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** AEROSOLS

**Proper shipping name (IMDG)** AEROSOLS

**Proper shipping name (ICAO)** AEROSOLS

**Proper shipping name (ADN)** AEROSOLS



## Chemodex Limited - Chemcut Metal Working Compound 500ml Aerosols

### 14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

#### Transport labels



### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

#### Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
<b>EU legislation</b>	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

Revision date 16/07/2015

## Chemodex Limited - Chemcut Metal Working Compound 500ml Aerosols

<b>Revision</b>	1
<b>SDS number</b>	4847
<b>Hazard statements in full</b>	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated H280 Contains gas under pressure; may explode if heated. H301 Toxic if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H331 Toxic if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H370 Causes damage to organs . H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.